

SUMMIT HILL

FINE CUSTOM WOOD PRODUCTS

Shoji Specifications

(See page 6 of “Installation Types” for sliding panel configurations and shoji track details.)

Standard Panel Dimensions

Panel thickness: 1-5/16”

Top rail & stiles: 1-3/4”

Bottom rail: 3”

Solid panel bottom: 12”-15” high x 1/2” thick flat panel

Grillework: 7/16”-3/4” wide x 3/8” thick (determined by panel size)

Header/Return/Fascia Dimensions

<u># of Tracks</u>	<u>Inside Mount Header (1/2” thick)</u>	<u>Outside Mount Header (1-1/8” thick)</u>
1	2”	2” (plus casing if applicable)
2	3-1/2”	3-1/2” (plus casing)
3	5-1/4”	5-1/4” (plus casing)
4	7”	7” (plus casing)

- Returns (if needed) are supplied the same depth as the header.
- Top fascia is 3-1/2” x 7/16”.
- Top & bottom wood tracks with grooves are also available. Widths are the same as the headers shown above (match # of grooves to # of tracks).

Inserts

- Synskin: Thin, durable plastic & fiberglass material. White only.
- Plexiglas: 1/8” thick. White is standard. Can special order other colors.
- Black out: White fabric with rubber backing. Used between 2 pieces of synskin to achieve complete darkness.
- Customer may also supply their own insert.

Finishes (basswood is standard)

Black paint, white paint, clear lacquer, maple stain, walnut stain, rosewood stain, oriental teak stain. Custom woods and finishes are also available.

Summit Hill, Inc. 167 Gleahaven Road · Wayzata, MN. 55391

Toll Free: 888-262-3555 · Local: 952-224-7075 · Fax: 952-224-7077

www.summithillinc.com